



Polyester Patching Putty

Black Orange White Neutral

GEL TIME: 16-20 min @ 77°
VISCOSITY: Paste Consistency
COVERAGE: N/A
THIX INDEX: N/A
WEIGHT PER GAL: 9.2 lbs

FLASH POINT: 77° F
VOCs: 0.24 lbs/gal
MONOMER CONTENT: 3%
SHELF LIFE: 6 months @ 68° F
DUST FREE TIME: 30 min @ 77° F

product applications

- ✓ Repair of Surface Imperfection on Wood, Metal, composite Parts
- ✓ Beginning Step for Prestec Surface Repair Systems
- ✓ Marine, Tooling, and Automotive Application
- ✓ All Surfaces Fast Cure Sealer Composite Surfaces Prior to Topcoat
- ✓ All Surfaces Fast Cure Sealer
- ✓ Architectural Wood Crafts

product features

- ✓ Rapid and thorough cure
- ✓ Quickly fills deep scarred surfaces
- ✓ Easy to sand and prep for surface primer
- ✓ Zero (0) VOCs
- ✓ MEKP catalyzed
- ✓ Comes in neutral for easy color matching

application suggestions

- ✓ Catalyze at 2% w/ MEKP initiator (0.5 oz/quart)
- ✓ Optimum temperature of 77°F
- ✓ Allow full cure (2 hrs) prior to primer application



info@Cyracpc.com



www.Cyracpc.com



909.923.2226



909.259.5000