

Safety Data Sheet

Issue date: 01/01/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: **GARALEASE 915** IDH number: 548976

MOLD COATING Product type: Item number: 38413 Restriction of Use: None identified **United States** Region:

Contact information: Company address:

Telephone: (909) 223-9699 Lilly-RAM Chemical Company

TRANSPORT EMERGENCY Phone: CHEMTREC 16170 Cedar Lane Loop

1-800-424-9300 (toll free) Willis, TX 77378 USA Internet: www.lillyram.com

Contains one or more components for which a Toxic Substances Control Act (TSCA) Low Volume Exemption (LVE) applies. See Section 15.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

FLAMMABLE LIQUID AND VAPOR. DANGER:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1









Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly

closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective

gloves, eye protection, and face protection.

Response: IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair):

Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison control center or physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry

chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Dimethyl Ketone	67-64-1	75 - 80
Diacetone Alcohol	123-42-2	5 - 10
Toluene	108-88-3	5 - 10
Proprietary Resin	Proprietary	5 - 10

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If skin irritation persists, call a

physician. Wash clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get immediate medical attention.

Ingestion: Keep individual calm. Do not induce vomiting: contains petroleum distillates

and/or aromatic solvents. If vomiting occurs, prevent aspiration by keeping the

patient's head below the knees. Get immediate medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high

volume water jet.

Special firefighting procedures: Keep personnel upwind of fire. Wear self-contained breathing apparatus and

full protective clothing, such as turn-out gear. Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool.

Unusual fire or explosion hazards: Vapors may form explosive mixtures with air. Hydrocarbon solvents are

basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a significantly high level, sparks can form that may ignite vapors of flammable liquids. Do not handle or store near an open flame, heat or other

sources of ignition.

Hazardous combustion products:

Oxides of carbon. Irritating organic vapours. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. This product is insoluble in

water and will float on surface. Do not allow product to enter sewer or waterways. Advise authorities if product has entered or may enter sewers,

water sources or extensive land areas.

Clean-up methods: Ventilate area. Remove all sources of ignition. Keep upwind of the spilled

material and isolate exposure. Wear suitable protective clothing, gloves and eye/face protection. Use non-sparking tools for clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling: Do not breathe gas/fumes/vapor/spray. For operations where eye or face

contact could occur, provide safety shower and eyewash fountain. Avoid contact with eyes, skin and clothing. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer

of material. Wash thoroughly after handling.

Storage: For safe storage, store between 5 °C (41°F) and 25 °C (77°F)

Store away from heat, sparks, flames, or other sources of ignition. Keep

container closed.

For information on product shelf life contact Lilly-RAM Customer Service at (909) 223-9699.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TWA	OSHA PEL	ACGIH STEL	OTHER
Dimethyl Ketone	500ppm	2400 mg/m3	750 ppm	1000 ppm
Diacetone Alcohol	50 ppm	240 mg/m3	50 ppm	None
Toluene	100 ppm	560 mg/m3	150 ppm	500 ppm
Proprietary Resin	None	None	None	None

Engineering controls: Use explosion-proof mechanical ventilation and local exhaust to control

contaminants to within their occupational exposure limits during the use of this

product.

Respiratory protection: Use a NIOSH approved supplied air respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:BlueOdor:mild, SolventOdor threshold:Not available

Odor threshold: Not available. PH: Not available.

Vapor pressure: 182 mmHG @ 68° F (20° C)

Roiling point/range: 56 °C (133 °F)

Boiling point/range: 56 °C (133 °F)
Melting point/ range: Not determined

Specific gravity: 0.82 Vapor density: 4

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Auto ignition temperature:

Notdetermined
Not available.

Evaporation rate: 5.6
Solubility in water: Not miscible
Partition coefficient (n-octanol/water): Not available.

VOC content: 17-octanon/water). Not available. 99.25 %; 749 g/l

10. STABILITY AND REACTIVITY

Stability: Risk of ignition may form explosive peroxides with prolonged exposure to air or oxygen,

especially under anhydrous conditions. Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Peroxides. Hydrocarbons.

Incompatible materials: Strong acids and strong bases. Strong oxidizing agents. Reacts with air to form peroxides.

Reactivity: Not available.

Conditions to avoid: Avoid static discharge. Will slowly degrade with exposure to oxygen (air). Spray mist may be

flammable at temperatures below the flash point. Keep away from open flames, hot surfaces and sources of ignition. Vapors may form explosive mixtures with air. Fire or intense heat may

cause violent rupture of packages. Direct sunlight.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Skin contact:

Inhalation: Vapors and mists will irritate nose and throat and possibly eyes. High vapor concentrations

(greater than approximately 1000 ppm) may cause headaches, dizziness, anesthesia,

drowsiness, unconsciousness, and other central nervous system effects, including death. Causes skin irritation. Solvent action can dry and defat the skin, causing the skin to crack,

leading to dermatitis.

Eye contact: Causes serious eye irritation.

Ingestion: This product may be fatal if it is swallowed. Aspiration may occur during swallowing or vomiting,

resulting in lung damage. Central nervous system depression, including dizziness, drowsiness,

fatigue, nausea, headache, unconsciousness.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Dimethyl Ketone	Inhalation LC50 (RAT, 4h) = 71 mg/l/	Irritant
Diacetone Alcohol	Inhalation LC50 (RAT, 4h) 10 mg/l	Irritant, Central nervous system, Cardiac, Kidney, Gastrointestinal, Mutagen
Toluene	Inhalation LC50 (RAT, 4 h) = 12500 mg/m3	Lung irritation, chest pain, pulmonary edema, central nervous system
Proprietary Resin	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Dimethyl Ketone	No	No	No
Diacetone Alcohol	No	No	No
Toluene	No	No	No
Proprietary Resin	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Paint Hazard class or division: 3
Identification number: UN 1263
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Paint
Hazard class or division: 3
Identification number: UN 1263
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: Paint
Hazard class or division: 3
Identification number: UN 1263
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components of this product are listed on the U.S. Toxic Substances Control Act (TSCA)

inventory or are exempt from listing because a Low Volume Exemption (LVE) has been

granted in accordance with 40 CFR 723.50.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health, Fire

CERCLA/SARA Section 313: None above reporting de minimis

CERCLA Reportable quantity: Dimethyl Ketone (CAS# 67-64-1 5000 lbs. (2250kg)

Toluene (CAS# 108-88-3 1000 lbs. (450kg)

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Chase Williams

Issue date: 01/01/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Lilly-RAM Corporation and its affiliates ("Lilly-RAM") does not assume responsibility for any results obtained by persons over whose methods Lilly-RAM has no control. It is the user's responsibility to determine the suitability of Lilly-RAM's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Lilly-RAM's products. In light of the foregoing, Lilly-RAM specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Lilly-RAM's products. Lilly-RAM further disclaims any liability for consequential or incidental damages of any kind, including lost profits.